



Neste Pneumatic 100

Oil for pneumatic tools



Excellent anti wear properties



Low oil mist



Excellent adhesion

Performance claims

ISO VG 100, ISO-L-PAC

Neste Pneumatic 100 is made of highly-refined mineral base oils and additives for stronger oil film, better wear resistance, better adhesion to metal surfaces and higher corrosion resistance. The additives also absorb water, prevent ice formation and improve the capillary penetration of the oil.

Applications

Neste Pneumatic 100 is suitable for large compressed-air machinery, e.g. rock drill machines in mines. For this application, Neste Pneumatic 46 is recommended instead during wintertime in outdoor use.

Typical properties

Density 15 °C	885	kg/m ³	ASTM D4052
Viscosity @ 40 °C	100	cSt	ASTM D445
Viscosity @ 100 °C	11,6	cSt	ASTM D445
Viscosity Index	104		ASTM D2270
Flash Point (COC)	225	°C	ASTM D92
Pour Point	-24	°C	ASTM D5949
Rust B	pass		ASTM D665

Yrityksille

Neste Oyj

Asemahaku

Oma Neste

Asemat	Tiedotteet ja uutiset
Tuotteet	Häiriötiedotteet
Asiakkuus ja edut	Neste-äppi
Ideat ja vinkit	Saavutettavuusseloste
Asiakaspalvelu ja tuki	

