



Neste Pro Gear 75W-80

Fully synthetic manual transmission oil

- ✓ Extra wide operating temperature area
- ✓ Excellent EP properties
- ✓ Good oxidation stability

Performance claims

API GL-4, DAF, Eaton/Fuller Europe Extended drain (300.000 km), **Iveco** 18-1807 MGS, **Iveco** 18-1807 MGS1, **MAN** 341 Type E3, **MAN** 341 Type E4, **MAN** 341 Type Z3, **MAN** 341 Type Z4, **MB** 235.4, **Volvo** 97307, **ZF** TE-ML 08, **ZF** TE-ML 13, **ZF** TE-ML 24A, **NSN** 9150-58-001-9658

Approvals

ZF TE-ML 01L **ZF** TE-ML 02L **ZF** TE-ML 16K

Neste Pro Gear 75W-80 is made of a fully synthetic base liquid blended with additives for EP, oxidation and rust resistance. In addition, it has excellent cold resistance, which allows for immediate smooth gear operation even at the most severe below-zero temperatures and efficient lubrication in hot operating conditions.

Applications

Recommended year a round use for MAN, Renault, Iveco and DAF heavy duty manual ZF transmissions. Please use car manufacture service manual to check drive line oil requirements and service intervals. Neste Pro Gear 75W-80 is also suitable for Volvo I-Shift transmissions.

Typical properties

Density 15 °C	857	kg/m ³	ASTM D4052
Viscosity @ 40 °C	59	cSt	ASTM D445
Viscosity @ 100 °C	9,8	cSt	ASTM D445
Viscosity Index	153		ASTM D2270
Pour Point	-39	°C	ASTM D5949
Brookfield Viscosity @ -40 °C	47 000	cP	ASTM D2983

Yrityksille

Neste Oyj

Asemahaku

Oma Neste

Asemat

Tiedotteet ja uutiset

Tuotteet

Häiriötiedotteet

[Asiakkuus ja edut](#)

[Neste-äppi](#)

[Ideat ja vinkit](#)

[Saavutettavuusseloste](#)

[Asiakaspalvelu ja tuki](#)

[© Neste](#)

[Evästeet](#)

[Hallitse evästeitä](#)

[Käyttöehdot](#)

[Tietosuoja](#)

[Ilmoita epäkohdasta](#)

[Modernin orjuuden lausunto](#)

